

Please keep in mind that most of this cheats are only working when you have included the Netbeans-Settingsfile from <http://www.symfony-zone.com/wordpress/netbeans/>

## Keyboard-Shortcuts

Shortcut	Action	Shortcut	Action
<b>Strg + Shift + 1</b>	Show File in Project-View	<b>Strg + Shift + Minus</b>	Collapse All
<b>Strg + Alt + c</b>	symfony cc	<b>Strg + Minus</b>	Collapse Fold
<b>Strg + Alt + r</b>	Run Symfony task	<b>Strg + Shift + Plus</b>	Expand All
<b>Strg + Alt + j</b>	Symfony Jump to View / Action	<b>Strg + Plus</b>	Expand Fold
<b>Alt + Shift + o</b>	Go to file	<b>Strg + R</b>	Rename
<b>Strg + O</b>	Go to type		

## Code Templates Controller

Short	Filetype	Trigger	Sourcecode
<b>Prr</b>	PHP	Tab	<pre>echo "&lt;pre&gt;"; print_r(\${cursor}); echo "&lt;/pre&gt;";</pre>
<b>Execute</b>	PHP	Tab	<pre>/**  * Action \${name}  */ public function execute\${name}(sfWebRequest \$request) {     \${cursor} }</pre>
<b>success</b>	PHP	Tab	<pre>return sfView::SUCCESS;</pre>
<b>none</b>	PHP	Tab	<pre>return sfView::NONE;</pre>
<b>getuser</b>	PHP	Tab	<pre>\$this-&gt;getUser()</pre>
<b>layout</b>	PHP	Tab	<pre>\$this-&gt;setLayout(\${cursor});</pre>
<b>template</b>	PHP	Tab	<pre>\$this-&gt;setTemplate(\${cursor});</pre>
<b>parameter</b>	PHP	Tab	<pre>\$request-&gt;getParameter('\${cursor}'\${cursor});</pre>
<b>attribute</b>	PHP	Tab	<pre>\$this-&gt;getUser()-&gt;getAttribute('\${cursor}'\${cursor});</pre>

## Code Templates View

Short	Filetype	Trigger	Sourcecode
<b>__</b>	PHP	Tab	<pre>__('\${cursor}');</pre>
<b>__</b>	HTML	Tab	<pre>&lt;?php echo __('\${cursor}'); ?&gt;</pre>
<b>slot</b>	HTML	Tab	<pre>&lt;?php slot('\${cursor}'); ?&gt; \${cursor} &lt;?php end_slot();?&gt;</pre>
<b>ipart</b>	HTML	Tab	<pre>&lt;?php include_partial('\${cursor}', array(\${cursor}));?&gt;</pre>
<b>ijs</b>	HTML	Tab	<pre>&lt;?php include_javascript('\${cursor}');?&gt;</pre>
<b>tif</b>	HTML	Tab	<pre>&lt;?php if(\${condition}):?&gt;     \${cursor} &lt;?php endif; ?&gt;</pre>
<b>tfe</b>	HTML	Tab	<pre>&lt;?php foreach(\${source} as \${value}):?&gt;     \${cursor} &lt;?php endif; ?&gt;</pre>
<b>ufo</b>	HTML	Tab	<pre>&lt;?php echo url_for('\${route}\${cursor}');?&gt;</pre>

## Code Templates schema.yml (Doctrine)

Short	Filetype	Trigger	Sourcecode
<b>tstring</b>	YAML	Tab	{ type: string({cursor}) }
<b>tint</b>	YAML	Tab	{ type: integer({cursor}) }
<b>tboolean</b>	YAML	Tab	{ type: boolean }
<b>tdouble</b>	YAML	Tab	{ type: double }
<b>ts</b>	YAML	Tab	Timestampable: ~
<b>type</b>	YAML	Tab	{ type: \${cursor} }